

ENVIRONMENT DATA SHEET

ECOSYS P4040dn



> Safety Approvals	EN 60950 / 60825 EMC: EN 55022 / 55024 / 61000
> Environment Certificates	ENERGY STAR, RoHs
> Power Consumption	Maximum (incl. options): 1,466 W Printing: 642 W Ready: 14 W Sleeping: 1.5 W Off: 0.5 W
> TEC (ENERGY STAR 2.0)	2.720 kWh
> Installation Notes	The unit should be placed in a way, that adequately space for operation and maintenance on both sides, as well as in front and behind the system is existing. Provide good ventilation. Do not place the unit in a dusty room, and protect against ammonia vapours. Please follow the instructions in the user manual.
> Room Humidity	15% to 80%
> Room Temperature	10.0°C to 32.5°C
> Noise Level	According to ISO 7779 / ISO 9296 or RAL-UZ 171 Printing ⁽¹⁾ : 50.4 dB(A) L _{pA} Ready ⁽¹⁾ : < Detection limit Printing ⁽²⁾ : 54.2 dB(A) L _{pA} Ready ⁽²⁾ : < Detection limit Printing: 66.1 dB(A) L _{Wad} Ready: < Detection limit L _{pA} = Sound Pressure Level L _{WA} = Sound Power Level L _{Wad} = Assured Sound Power Level ⁽¹⁾ Surface sound pressure level measurement 1 m distance ⁽²⁾ Operator position
> Light Source	Exposure Drum Laser
> Emissions	According to RAL-UZ 171 TVOC (Operation): 9.0 mg/h TVOC (Ready): 0.15 mg/h Benzene: < Detection limit Styrene: 0.12 mg/h Ozone: 0.60 mg/h Fine Dust: 0.35mg/h